



- High driving power, excellent load performance, anti-skid, less friction heat.
- Use new rubber formula, low heat generation, more fuel-efficient.

SM991

TBR SPECIFICATION

SIZE	PATTERN NAME	TREAD DEPTH (mm)	WEIGHT (kg)	PR	LI	SS	Rim	Max Load		Max Pressure		OD (mm)	SW (mm)
								(kg)	(lbs)	(kPa)	(psi)		
11R22.5	SM991	22	55	18PR	149/146	L	8.25	3000	2725	830	120	1059	279
11R24.5	SM991	22	58.5	18PR	149/146	M	8.25	3250	3000	830	120	1110	279
295/75R22.5	SM991	21.5	53.6	16PR	146/143	M	9.00	3000	2735	830	120	1020	298



- High driving power, excellent load performance, anti-skid, less friction heat.
- Use new rubber formula, low heat generation, more fuel-efficient.

SM996

TBR SPECIFICATION

SIZE	PATTERN NAME	TREAD DEPTH (mm)	WEIGHT (kg)	PR	LI	SS	Rim	Max Load		Max Pressure		OD (mm)	SW (mm)
								(kg)	(lbs)	(kPa)	(psi)		
11R22.5	SM996	15	52	18PR	149/146	L	8.25	3000	2725	830	120	1054	279
11R24.5	SM996	15	55.2	18PR	149/146	M	8.25	3250	3000	830	120	1104	279
295/75R22.5	SM996	14.5	50.5	16PR	146/143	M	9.00	3000	2735	830	120	1014	298